

# **HANDLE-IT®** RA Series



Part Number: SWM-RA-2300

250% Power Pre-Stretch Carriage
300 max average pallets per day!
Designed for heavy throughput

| Technical Specifications |                        |
|--------------------------|------------------------|
| Wrap Height              | 94"                    |
| Machine Dimensions       | 181"L x 121" w x 122"h |
| Max Pallet Size          | 40" x 48"              |
| Weight Capacity          | Unlimited              |
| Pre-Stretch              | 250% Powered           |
| Power Supply             | 110V, 10 Amp           |
| Total Machine Footprint  | 93" long x 60" wide    |
| Machine Weight           | 2000lbs                |
| Turntable Speed          | 12 RPM                 |
|                          |                        |

### Handle-It® Model 2300

The Handle-It® *Model 2300* offers top-of-the-line functions and features at a great price. It is ideal for those who are looking for an efficient machine capable of handling high volumes of pallets per day.

Standard features on the 2300 include 250% powered pre-stretch, 94" max wrap height, user-friendly control panel, electronic film tension, and many other elements cleverly designed to make this unit a must-have in any facility looking to improve and streamline their packaging operations.



## **HANDLE-IT®**


# Automatic Stretch Wrapper

#### **Product Specifications**

- Electronic printed circuit board for the management of the cycle
- Frequency controller for rotation speed adjustment (from 3 to 12 RpM)
- 250% Powered Pre-stretch Film Carriage
- Frequency controller for carriage speed adjustment (speed going up and speed going down can be set differently)
- Maximum wrapping height: 94"
- Maximum size of the pallet: 40" x 48"
- Maximum loading weight: Unlimited
- Electromagnetic brake for film stretching
- Photocell for pallet height detection
- Safety stop loop at the base of the carriage
- Stop at 0 position
- Power board IP54
- 3 access keys (including lock mode)
- Adjustable parameters by the control panel: cycle selection, bottom turns, top turns, rotation speed, carriage speed going up, carriage speed going down, film tension.
- 6 working cycles: ascent/descent; topsheet; only ascent; only descent; layers; stack
- 32 wrap programs can be saved by the customer
- 3 cycle types: semimanual, semiautomatic, and fixed height
- Acoustic warning at the cycle beginning and stop
- Wrapped Pallet counter
- Autodiagnostic
- **Powder coating**
- Braked arm at the end of the cycle
- Adjustable power pre-stretch
- Photocell for Dark Loads
- Extended mast 118"
- **Extended Arm for larger pallets**



Intuitive Control Board



HANDLE !









